# **Trimble TSC7**

# CONTROLLER

### **KEY FEATURES**

- Optimized for Trimble® Access™ field software
- Large 7-inch multi-touch screen for finger or stylus
- Sunlight readable display
- Secure Windows® 10 Pro operating system
- Compatible with Microsoft® Office, web browsers, and other third-party apps
- Manages large project files, complex imagery, point clouds, and other 3D data
- ► Intel Pentium processor with 8 GB RAM and 64 GB internal memory
- ► Comprehensive connectivity options
- Front- and rear-facing cameras
- Backlit keypad with customizable button commands
- ► User-interchangeable EMPOWER modules, including a long-range radio
- Military-spec rugged design, engineering and performance
- ► Ergonomic form factor
- ► Hot-swappable batteries with LED indicators

Learn more: geospatial.trimble.com/TSC7





# **Trimble TSC7** CONTROLLER

| PHYSICAL SPECIFICATIONS |   |  |
|-------------------------|---|--|
| Size                    | 30 x 20.9 x 7.1 cm (11.8 x 8.2 x 2.8 ")                   |  |
| Weight                  | 1.42 kg (3.12 lb)   |  |
| Housing                 | Glass-fibre reinforced resin with integrated drop bumpers |  |

| ENVIRONMENTAL SPECIFICATIONS<br>(meets or exceeds) |   |  |
|--|---|--|
| Operating temperature                              | -20 °C to 60 °C (-4 °F to 140 °F)<br>MIL-STD-810G 501.5 Procedures II (operation)                                   |  |
| Storage temperature                                | -40 °C to 70 °C (-40 °F to 158 °F)<br>MIL-STD-810G 501.5 Procedures I (storage)                                     |  |
| Humidity   | 90 % RH temp cycle –20 °C/60 °C (–4 °F/140 °F)<br>MIL-STD-810G, Method 507.5, Procedure II                          |  |
| Sand & dust  | IP6x: 8 hours of operation with blowing talcum powder (IEC-529)   |  |
| Water  | IPx8: Immersion, up to 1 m (3.2 ft) depth for 2 hours   |  |
| Drop   | 26 drops at room temperature from 1.22 m (4 ft) onto plywood over concrete MIL-STD-810G, Method 516.6, Procedure IV |  |

| SECURITY                      |  |
|-------------------------------|--|
| TPM (Trusted Platform Module) |  |

| CONFIGURATIONS                     |  |
|------------------------------------|--|
| EMPOWER module support             | 2 x module bays  |
| Languages supported at first boot: | Chinese (Simplified), English (US), French, German,<br>Italian, Japanese, Korean, Portuguese (Brazilian),<br>Spanish (Castilian region and Mexico) |

|               | CERTIFICATIONS   |
|---------------|--|
| Among others  | FCC, NRTL, ICES, IC, NRTL, CE, CB, RCM, CCC  |
| Countries     | Certified in countries: USA, Canada, EU, Australia/<br>New Zealand, South Africa, India, Malaysia, Tunisia,<br>UAE, Thailand, Taiwan, Russia |
| Environmental | EU RoHS, China RoHS, REACH, WEEE   |

#### COMPATIBLE FIELD SOFTWARE

Trimble Access version 2017.2x and Trimble Access version 2018 and later

| ELEC.                       | TRICAL SPECIFICATIONS   |
|-----------------------------|---|
| Processor                   | Intel Apollo Lake - N4200, 64-bit quad-core   |
| Memory                      | 8 GB RAM, LPDDR4  |
| Storage                     | 64 GB eMMC  |
| Expansion                   | via microSDXC card up to 2 TB   |
| Batteries                   | $2\times3100$ mAh (22.53 Wh) min. capacity/3150 mAh (22.90 Wh) nominal capacity; removable, hot swappable, charge LED indicator             |
| Battery life                | Medium usage approx. 5 hours, can range 4–7 hours (depending on display settings, connectivity, data processing, ambient temperature, etc.) |
| Charging time               | Full-charge 3.5 hours, fast-charge (80 %) 1 ¾ hours   |
| Power input                 | 19V/5A charging   |
| Notification LED            | Charging and power status   |
| Display                     | 7-inch, 1280 x 800 landscape, 16:10, multi-point capacitive, 650+ nits sunlight readable  |
| Keyboard                    | QWERTY or ABCD, with backlight, numeric key block, Fn keys (6 physical + 6 2nd function Fn keys)  |
| Audio                       | Speaker and dual digital microphone array with noise reduction  |
| External speaker/microphone | 3.5 mm mini-jack or wireless headset  |
| 1/0                         | User replaceable module.<br>Standard: Charger/DC power-in, USB 3.1 Gen 1 type<br>A host, serial RS232 DB-9                                  |
| USB                         | USB 3.1 Gen 1   |
| WWAN                        | Worldwide LTE in regions where it is available,<br>and compatible with 3G networks<br>AT&T and Verizon certified. MicroSIM card             |
| Wi-Fi                       | 802.11 a/b/g/n, 2.4 GHz radio band  |
| Bluetooth®                  | BT 2.1 + EDR, BT 4.1  |
| Camera                      | Rear camera 8 MP autofocus with flash<br>Front camera 2 MP fixed-focus  |
| GNSS                        | Integrated GNSS   |
| Sensors                     | 3-axis accelerometer, magnetic sensor, ambient light sensor, proximity sensor   |

Specifications subject to change without notice.

















Seiler Instrument Company St. Louis \* Kansas City \* Milwaukee \* Indianapolis \* Omaha Toll Free: 888-263-8918 or contact us at: www.seilergeo.com/contact-us/

© 2018, Trimble Inc. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Inc., registered in the United States and in other countries. Access is a trademark of Trimble Inc. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. PN 022516-365A (04/18)

